



The NEW "Viscous-Damped"

GRAY 108-B ARM



Patent
applied for



1st BASIC ADVANCE IN DECADES

For All Records-33 $\frac{1}{3}$, 45 & 78 RPM Satisfies ALL Requirements of Micro-Groove Reproduction

A radically NEW design, the GRAY 108-B Transcription Arm represents a far-reaching advance in suspension principle for perfect tracking of records and virtual elimination of tone arm resonances. It satisfies every requirement of LP reproduction. The plug-in feature permits instantaneous changing from 78-rpm to LP (micro-groove) or 45-rpm records, with correct stylus pressure automatically obtained. Will accommodate all the most popular magnetic pick-up cartridges — Pickering, the new GE replaceable stylus (short body). This NEW Gray 108-B Tone Arm is the long-sought solution to all transcription problems.

- 1) Perfect tracking of records.
- 2) Lowest stylus pressure (5 grams).
- 3) No groove-jumping at fundamental resonance frequency.
- 4) Adjustable for degree of damping.
- 5) Prevents damage due to dropping.
- 6) Perfect contact with bad records.
- 7) For 33 $\frac{1}{3}$, 45 & 78 RPM records.
- 8) Cartridges changed instantaneously.
- 9) Automatically correct stylus pressure.
- 10) Accommodates most variable reluctance cartridges.
- 11) For records up to 16" diameter.

106-SP TRANSCRIPTION ARM

Designed to meet the strict requirements of modern highly compliant pick-up cartridges. 3 cartridge slides furnished enable GE 1-mil, 2 $\frac{1}{2}$ -mil or 3-mil cartridges or Pickering cartridge to be slipped into position in a jiffy. No tools or solder! Finest reproduction of 33 $\frac{1}{3}$, 45 or 78-rpm records with ONE transcription arm. Precisely adjustable stylus pressure.

103-S TRANSCRIPTION ARM

This Gray arm is specifically designed and engineered for conventional 78-rpm records. Built of feather-light magnesium, the 103-S guarantees exceptionally faithful reproduction. Its excellent performance is recognized by leading audio engineers.

103-LP TRANSCRIPTION ARM

The Gray LP Arm, with finest angular contact ball-pivot, is recommended for 33 $\frac{1}{3}$, 45 or conventional 78-rpm records. Adjustable counterweight permits accurate setting of precise stylus pressure for Micro-Groove records.

SEE YOUR LOCAL DISTRIBUTOR OR WRITE

GRAY RESEARCH and Development Co., Inc.

658 Hilliard Street, Manchester, Conn.

