



BAUER COMMUNICATIONS, INC.

PRECISION TRANSFORMERS

By Reichenbach Engineering

1090

	1	12	25	50	75	100	250	500	1000
MICROPHONE INPUT									
RE-110K-C	40.21	36.78	33.34	30.22	27.91	25.64	23.43	21.28	19.19
<u>RE-110K-CU</u>	33.77	30.89	28.00	25.38	23.43	21.53	19.68	17.87	16.11
RE-110K-FA	47.16	43.14	39.11	35.45	32.73	30.08	27.48	24.96	22.50
<u>RE-110K-FB</u>	45.65	41.76	37.85	34.31	31.68	29.11	26.60	24.16	21.78
<u>RE-115K-E</u>	49.01	44.84	40.64	36.84	34.02	31.26	28.56	25.94	23.39
RE-135K-D	49.68	45.44	41.19	37.34	34.48	31.68	28.95	26.29	23.70
<u>RE-13K6-C</u>	40.21	36.78	33.34	30.22	27.91	25.64	23.43	21.28	19.19
<u>RE-13K7-A</u>	63.01	57.64	52.24	47.35	43.73	40.18	36.71	33.35	30.06
RE-13K7-B	71.24	65.17	59.07	53.55	49.44	45.43	41.51	37.71	33.99
RE-150MM	9.43	8.63	7.82	7.09	6.55	6.02	5.50	4.99	4.50
<u>RE-16-A</u>	63.01	57.64	52.24	47.35	43.73	40.18	36.71	33.35	30.06
<u>RE-16-B</u>	69.26	63.36	57.43	52.06	48.07	44.17	40.36	36.66	33.05
RE-6110K-A	41.50	37.96	34.41	31.19	28.80	26.47	24.18	21.96	19.80
MICROPHONE INPUT PC TYPE									
<u>RE-110K-HPC</u>	47.35	43.31	39.26	35.59	32.86	30.20	27.59	25.06	22.59
RE-115K-MAX	41.12	37.62	34.10	30.91	28.54	26.23	23.96	21.77	19.62
RE-13K7-APC	76.81	70.26	63.69	57.73	53.31	48.98	44.76	40.65	36.65
RE-150K-MAX	30.31	27.72	25.13	22.78	21.03	19.33	17.66	16.04	14.46
RE-16-APC	76.81	70.26	63.69	57.73	53.31	48.98	44.76	40.65	36.65
RE-6110K-APC	40.87	37.39	33.89	30.72	28.37	26.07	23.82	21.63	19.50
MICROPHONE BRIDGING									
<u>RE-MB-C</u>	39.58	36.21	32.82	29.75	27.47	25.24	23.06	20.95	18.89
RE-MB-CPC	51.50	47.11	42.70	38.71	35.74	32.84	30.01	27.26	24.57
<u>RE-MB-CSC</u>	45.87	41.96	38.04	34.48	31.84	29.25	26.73	24.28	21.89
<u>RE-MB-D</u>	69.23	63.33	57.41	52.03	48.05	44.15	40.34	36.64	33.03
RE-MB-DLL	73.76	67.47	61.16	55.44	51.19	47.04	42.98	39.04	35.19
<u>RE-MB-E</u>	95.58	87.43	79.25	71.84	66.33	60.95	55.69	50.59	45.60
DIRECT BOX									
<u>RE-DB-E</u>	49.68	45.44	41.19	37.34	34.48	31.68	28.95	26.29	23.70
RE-DB-EPC	51.50	47.11	42.70	38.71	35.74	32.84	30.01	27.26	24.57
RE-DB-EU	46.09	42.16	38.22	34.64	31.99	29.39	26.86	24.39	21.99
LINE INPUT									
<u>RE-10KB-B</u>	59.55	54.47	49.38	44.76	41.33	37.97	34.70	31.52	28.41
<u>RE-10KB-C</u>	41.94	38.37	34.78	31.52	29.11	26.75	24.44	22.20	20.01
<u>RE-11P-1</u>	46.66	42.68	38.69	35.07	32.38	29.75	27.19	24.69	22.26
<u>RE-11P-1D</u>	51.18	46.82	42.44	38.47	35.52	32.64	29.82	27.09	24.42
RE-11P-1T	48.13	44.03	39.91	36.18	33.41	30.70	28.05	25.48	22.97
<u>RE-11P-2</u>	86.82	79.41	71.98	65.24	60.25	55.36	50.58	45.94	41.42
<u>RE-11P-5</u>	65.77	60.17	54.54	49.43	45.65	41.94	38.33	34.81	31.38
<u>RE-11P-9</u>	102.12	93.41	84.68	76.75	70.87	65.12	59.50	54.05	48.72
<u>RE-11SSP-6M</u>	82.22	75.21	68.17	61.79	57.06	52.43	47.91	43.51	39.22
<u>RE-11SSP-8M</u>	162.61	148.75	134.83	122.21	112.85	103.70	94.75	86.06	77.58
RE-11SSP-8MA	134.53	123.06	111.55	101.11	93.37	85.79	78.39	71.20	64.19
<u>RE-6110K-B</u>	65.71	60.11	54.49	49.39	45.60	41.90	38.29	34.78	31.35
RE-6110K-BB	71.49	65.40	59.28	53.73	49.62	45.59	41.66	37.84	34.11
RE-751-M	93.75	85.76	77.74	70.46	65.07	59.79	54.63	49.62	44.73

	1	12	25	50	75	100	250	500	1000
LINE INPUT PC OR OCTAL BASE									
RE-10KB-BPC	74.61	68.25	61.86	56.07	51.78	47.58	43.47	39.49	35.60
RE-11P-1AN	64.92	59.39	53.83	48.80	45.06	41.40	37.83	34.36	30.98
RE-11P-1B	59.55	54.47	49.38	44.76	41.33	37.97	34.70	31.52	28.41
RE-11P-1BN	64.92	59.39	53.83	48.80	45.06	41.40	37.83	34.36	30.98
<u>RE-11P-1CST</u>	64.92	59.39	53.83	48.80	45.06	41.40	37.83	34.36	30.98
<u>RE-11P-1PC</u>	45.24	41.39	37.51	34.00	31.40	28.85	26.36	23.94	21.59
<u>RE-11P-1QN</u>	64.92	59.39	53.83	48.80	45.06	41.40	37.83	34.36	30.98
<u>RE-11P-FLAPC</u>	31.28	28.62	25.94	23.51	21.71	19.95	18.23	16.56	14.93
RE-11SSP-6MP	103.09	94.30	85.48	77.48	71.55	65.74	60.07	54.56	49.19
RE-6110K-BPC	81.74	74.78	67.78	61.44	56.73	52.13	47.63	43.26	39.00
<u>RE-900-9050</u>	64.92	59.39	53.83	48.80	45.06	41.40	37.83	34.36	30.98
RE-900-9150	115.92	106.04	96.12	87.12	80.45	73.92	67.55	61.35	55.30
RE-900-9155	59.74	54.64	49.53	44.90	41.46	38.10	34.81	31.62	28.50
<u>RE-8043</u>	45.24	41.39	37.51	34.00	31.40	28.85	26.36	23.94	21.59

OUTPUT STEEL CORE

RE-11-FCF	22.29	20.39	18.48	16.75	15.47	14.22	12.99	11.80	10.64
RE-112-CF	24.02	21.97	19.92	18.05	16.67	15.32	14.00	12.71	11.46
<u>RE-123-ACF</u>	33.61	30.74	27.87	25.26	23.33	21.43	19.58	17.79	16.04
RE-123-B	38.36	35.09	31.81	28.83	26.62	24.46	22.35	20.30	18.30
RE-123-D	34.05	31.15	28.23	25.59	23.63	21.71	19.84	18.02	16.25
RE-123-H	34.58	31.64	28.68	25.99	24.00	22.06	20.15	18.30	16.50
<u>RE-123-SCF</u>	27.16	24.85	22.52	20.42	18.85	17.32	15.83	14.38	12.96
RE-8093	139.91	127.98	116.01	105.15	97.10	89.22	81.52	74.05	66.75

OUTPUT STEEL CORE PC TYPE

RE-11-FPC	22.95	20.99	19.03	17.25	15.93	14.64	13.37	12.15	10.95
<u>RE-112-PC</u>	24.68	22.58	20.46	18.55	17.13	15.74	14.38	13.06	11.78
RE-123-APC	34.27	31.35	28.42	25.76	23.78	21.85	19.97	18.14	16.35
RE-123-SPC	28.89	26.43	23.96	21.72	20.05	18.43	16.84	15.29	13.79
<u>RE-123-C</u>	33.61	30.74	27.87	25.26	23.33	21.43	19.58	17.79	16.04
RE-125-SPC	33.17	30.34	27.50	24.93	23.02	21.15	19.33	17.56	15.83
RE-DBX	25.09	22.95	20.80	18.86	17.41	16.00	14.62	13.28	11.97

OUTPUT 50% NICKEL CORE

<u>RE-11-BLCF</u>	49.90	45.64	41.37	37.50	34.63	31.82	29.07	26.41	23.81
<u>RE-11-DLCF</u>	38.07	34.83	31.57	28.62	26.42	24.28	22.19	20.15	18.17
<u>RE-11-ELCF</u>	30.37	27.78	25.18	22.83	21.08	19.37	17.70	16.07	14.49
<u>RE-11-FLCF</u>	22.86	20.91	18.95	17.18	15.86	14.58	13.32	12.10	10.91
RE-11-FL X	40.93	37.45	33.94	30.77	28.41	26.11	23.85	21.67	19.53
<u>RE-11SL</u>	42.57	38.94	35.30	32.00	29.54	27.15	24.81	22.53	20.31
<u>RE-112-LCF</u>	27.42	25.08	22.73	20.61	19.03	17.48	15.98	14.51	13.08
RE-11SS-BLCF	57.79	52.86	47.92	43.43	40.11	36.85	33.67	30.58	27.57
RE-11SS-DLCF	44.80	40.98	37.15	33.67	31.09	28.57	26.11	23.71	21.38
RE-11SS-ELCF	36.85	33.71	30.55	27.69	25.57	23.50	21.47	19.50	17.58
RE-11SS-FLCF	30.72	28.10	25.47	23.09	21.32	19.59	17.90	16.26	14.66
<u>RE-123-ALCF</u>	42.57	38.94	35.30	32.00	29.54	27.15	24.81	22.53	20.31
<u>RE-123-BLCF</u>	54.52	49.87	45.21	40.97	37.84	34.77	31.77	28.85	26.01
<u>RE-123-DLCF</u>	42.60	38.97	35.32	32.02	29.57	27.17	24.82	22.55	20.33
RE-123-ELCF	33.74	30.86	27.97	25.35	23.41	21.51	19.66	17.85	16.10
<u>RE-123-FLCF</u>	27.42	25.08	22.73	20.61	19.03	17.48	15.98	14.51	13.08
RE-123-SLCF	33.74	30.86	27.97	25.35	23.41	21.51	19.66	17.85	16.10
RE-123-SL-X	51.81	47.40	42.96	38.94	35.96	33.04	30.19	27.42	24.72
RE-8251	47.03	43.02	39.00	35.35	32.64	29.99	27.41	24.89	22.44



BAUER COMMUNICATIONS, INC.

6887 Farmdale Avenue, Bldg.12, North Hollywood, CA 91605
 (800) 627-7277 (818) 891-9983 FAX (818) 894-0715

	1	12	25	50	75	100	250	500	1000
OUTPUT 50% NICKEL CORE PC TYPE									
<u>RE-123-ELPC</u>	35.40	32.38	29.35	26.61	24.57	22.58	20.63	18.74	16.89
<u>RE-11-FLPC</u>	27.98	25.60	23.20	21.03	19.42	17.84	16.30	14.81	13.35
RE-112-LPC	31.28	28.62	25.94	23.51	21.71	19.95	18.23	16.56	14.93
RE-123-FLPCA	31.28	28.62	25.94	23.51	21.71	19.95	18.23	16.56	14.93
RE-123-ALPC	43.23	39.55	35.85	32.49	30.00	27.57	25.19	22.88	20.63
RE-123-DBX	35.40	32.38	29.35	26.61	24.57	22.58	20.63	18.74	16.89
<u>RE-123-SLPC</u>	35.40	32.38	29.35	26.61	24.57	22.58	20.63	18.74	16.89

OUTPUT 80% NICKEL CORE

<u>RE-11-BMCF</u>	63.10	57.72	52.32	47.43	43.79	40.24	36.77	33.40	30.11
<u>RE-11-DMCF</u>	47.07	43.05	39.03	35.37	32.66	30.01	27.43	24.91	22.46
<u>RE-11-EMCF</u>	40.78	37.30	33.81	30.65	28.30	26.00	23.76	21.58	19.46
RE-11-FMCF	27.92	25.54	23.15	20.98	19.38	17.80	16.27	14.78	13.32
RE-11-GMCF	27.51	25.17	22.81	20.68	19.09	17.54	16.03	14.56	13.13
RE-112-MCF	32.48	29.71	26.93	24.41	22.54	20.71	18.92	17.19	15.50
RE-11SS-BMCF	68.63	62.78	56.91	51.58	47.63	43.77	39.99	36.33	32.75
RE-11SS-EMCF	45.93	42.02	38.09	34.52	31.88	29.29	26.77	24.31	21.92
<u>RE-123-BMCF</u>	67.72	61.95	56.15	50.90	47.00	43.19	39.46	35.84	32.31
RE-123-DMCF	51.66	47.25	42.83	38.82	35.85	32.94	30.10	27.34	24.65
RE-123-FMCF	32.48	29.71	26.93	24.41	22.54	20.71	18.92	17.19	15.50

OUTPUT 70v & 25v

RE-25VC-10W	52.06	47.63	43.17	39.13	36.13	33.20	30.34	27.56	24.84
RE-752-M	65.24	59.68	54.10	49.03	45.28	41.60	38.01	34.53	31.13
RE-70VC-5W	106.11	97.07	87.99	79.75	73.64	67.67	61.83	56.16	50.63

MOVING COIL INPUT

RE-34K-DX	64.26	58.79	53.29	48.30	44.60	40.98	37.45	34.01	30.66
RE-44K-DX	64.26	58.79	53.29	48.30	44.60	40.98	37.45	34.01	30.66

ELECTRET MICROPHONE OUTPUT

<u>RE-7552</u>	23.99	21.94	19.89	18.03	16.65	15.30	13.98	12.70	11.45
----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------

LOW FREQUENCY TAPPED INDUCTORS

RE-LX-2K	122.33	111.91	101.44	91.94	84.90	78.01	71.28	64.75	58.36
RE-LX-600	122.33	111.91	101.44	91.94	84.90	78.01	71.28	64.75	58.36
RE-7961	14.40	13.17	11.94	10.82	9.99	9.18	8.39	7.62	6.87
RE-8355	18.93	17.31	15.69	14.23	13.14	12.07	11.03	10.02	9.03

TAPE HEAD MATCH

RE-642-90	92.43	84.55	76.65	69.47	64.15	58.95	53.86	48.92	44.10
-----------	-------	-------	-------	-------	-------	-------	-------	-------	-------

TUBE INPUT

RE-91105	81.74	74.78	67.78	61.44	56.73	52.13	47.63	43.26	39.00
----------	-------	-------	-------	-------	-------	-------	-------	-------	-------

[123-BMCF]
61.76



BAUER COMMUNICATIONS, INC.

ALL TRANSFORMERS REPRESENTED IN THIS PRICE LIST ARE THE EXCLUSIVE DESIGN AND MANUFACTURE OF REICHENBACH ENGINEERING.

TERMS:

Prices, terms, and conditions subject to change without notice or obligation.

All prices are FOB North Hollywood, CA.

Each order is subject to acceptance by Bauer Communications, Inc. and Bauer Communications, Inc. may for any reason, reject the order, or any portion thereof.

OEM's (upon approval of credit) terms are as follows:

5% 10, net 30. 1.5% charged on all accounts past 30 days.

This privilege is cancelable and a return may be made to COD or CIA at any time.

Samples sent for evaluation must be returned within 30 days or you will be billed at the 1 piece price.

Yearly POs will be accepted for quantity discounts with flexible scheduled shipments.

Bauer Communications, Inc. will make every attempt to ship within a reasonable time span but shall not be liable to the customer for damages, incidental or consequential for failure to meet specified delivery requirements.

Bauer Communications shall have the right to make partial shipments of orders unless otherwise stated at time of order entry. Each partial shipment may be invoiced separately and shall be paid for when due, without regard to subsequent shipments. Delay in shipment or delivery of any particular installment shall not relieve the customer of its obligation to accept remaining installments.

Bauer Communications, Inc. hereby rejects any terms and conditions in any purchase order or other business forms which are different from or in addition to the terms stated herein, unless specifically accepted in writing by Bauer Communications, Inc.



BAUER COMMUNICATIONS, INC.

6887 Farmdale Avenue, Bldg.12, North Hollywood, CA 91605
(800) 627-7277 (818) 891-9983 FAX (818) 894-0715